

**MATERIAL SAFETY DATA SHEET**

**SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

<b>Product:</b>	DR-2, DR-2AB, DR-CH, DR-2GG, DRB-2	<b>Trade Name:</b>	Drill-Ease Stick Lubricant
<b>Manufacturer:</b>	AGS Company	<b>Common Name:</b>	Stick Lubricant
<b>Street Address:</b>	2651 Hoyt St		
<b>City/State/Zip</b>	Muskegon Hts., MI 49444		
<b>Phone:</b>	800-253-0403		
<b>Phone:</b>	231-733-2101		
<b>FAX:</b>	231-733-1784	<b>Original Issue Date:</b>	11/7/1981
<b>Transportation Emergency:</b>	CHEM-TEL	<b>Revision No.</b>	7 <b>Date</b> 1/29/2007
<b>Phone:</b>	800-255-3924		

**SECTION 2 - COMPOSITION/ INFORMATION ON INGREDIENTS**

ITEM	CAS NUMBER	WT/WT %
1 Mineral Oil Hydrotreated (Severe)	64742-52-5	15-40
2 Paraffin	64742-51-4	15-40

**EXPOSURE LIMITS**

ITEM	ACGIH		OSHA	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING
1	5 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	N.E.
2	2 mg/m <sup>3</sup> fume	N.E.	2 mg/m <sup>3</sup> fume	N.E.

(See Section 16 for abbreviation legend)

**SECTION 3 - HAZARDS IDENTIFICATION/EFFECTS OF OVEREXPOSURE**

**EYE CONTACT:** May be irritating and can cause pain, tearing, reddening and swelling.

**SKIN CONTACT:** Prolonged contact may result in irritation. In molten state product can cause burns.

**INHALATION:** None expected.

**INGESTION:** This material may be harmful if swallowed.

**CHRONIC HAZARDS:** There are no foreseeable uses of the product that would lead to chronic exposure.

**Primary Route(s) of Entry** Skin and eye contact or ingestion.

**SECTION 4 - FIRST AID MEASURES**

**EYE CONTACT:** Immediately flush eyes with plenty of water. Get medical attention, if irritation persists

**SKIN CONTACT:** Immediately flush with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

**INGESTION:** Get medical attention immediately. If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

**MATERIAL SAFETY DATA SHEET**  
SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT:	380°F C.O.C.	193°C	LOWER EXPLOSIVE LIMIT:	N.D.	%
			UPPER EXPLOSIVE LIMIT:	N.D.	%
AUTOIGNITION TEMPERATURE:	N.D.				
EXTINGUISHING MEDIA:	Alcohol foam, CO <sub>2</sub> Dry chemical, foam, water fog				
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Product can produce dense smoke from oils burning.				
SPECIAL FIREFIGHTING PROCEDURES:	Wear NIOSH/MSHA approved self-contained breathing apparatus and protective gear.				

SECTION 6 - ACCIDENTAL RELEASE MEASURES

RECOVERY PROCEDURES: Scrape up material and place in a chemical waste container.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Wash thoroughly after handling

STORAGE: Keep away from heat, sparks, and flame.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: No special controls needed when used in supplied form.

RESPIRATORY PROTECTION: For most conditions, no respiratory protection should be needed, however, if high vapor concentration should develop, use a NIOSH approved organic vapor respirator.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves.

EYE PROTECTION: Wear safety glasses with side shields or goggles.

OTHER PROTECTIVE EQUIPMENT: Eye wash in work area.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	572-575°F	300-302°C	VAPOR DENSITY:	Is heavier than air
ODOR	Petroleum		ODOR THRESHOLD	N.D.
APPEARANCE	Tan Wax, Solid		EVAPORATION RATE	Is slower than Butyl Acetate
SOLUBILITY IN H <sub>2</sub> O	Insoluble		MELT POINT	162°F, ASTM D127
FREEZE POINT	N.A.		SPECIFIC GRAVITY	0.75
VAPOR PRESSURE	N.D.		pH @ 0.0%	N.A.
PHYSICAL STATE	Solid		VISCOSITY:	N.A.
COEFFICIENT OF WATER / OIL DISTRIBUTION:	Negligible			
	(See Section 16 for abbreviation legend)			

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Sources of ignition.

INCOMPATIBILITY: Strong acid or alkali, oxidizers and amines.

**MATERIAL SAFETY DATA SHEET**

HAZARDOUS DECOMPOSITION PRODUCTS      Oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION:      Will not occur under normal conditions

STABILITY: This product is stable under normal storage conditions.

**MATERIAL SAFETY DATA SHEET**  
SECTION 11 - TOXICOLOGICAL PROPERTIES

PRODUCT LD-50 5000 mg/kg PRODUCT LC-50 No Data

COMPONENT TOXICOLOGICAL INFORMATION:

CHEMICAL NAME	LD50	LC50
Mineral Oil Hydrotreated (Severe)	N.D.	N.D.
Paraffin	5000 mg/kg/rat	N.E.
Microcrystalline Wax	N.E.	N.E.
Carnauba Wax	N.E.	N.E.
Naphthenic acid, zinc salt	N.E.	N.E.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No information

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all federal, state and local regulations.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME Not Regulated

DOT TECHNICAL NAME

DOT HAZARD CLASS HAZARD SUBCLASS:

DOT UN / NA NUMBER: PACKING GROUP: NA RESP. GUIDE PAGE

SECTION 15 - REGULATORY INFORMATION

U.S FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 cfr 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III ) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard

SARA SECTION 313

This product contains the following substance subject to the reporting requirements of Section 313 of Title of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME	CAS NUMBER	WT /WT % IS LESS THAN
Naphthenic acid, zinc salt	12001-85-3	1

TOXIC SUBSTANCE CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12 (B) if exported from the United States:

CHEMICAL NAME	CAS NUMBER
There are no components subject to TSCA 12(b)	

**MATERIAL SAFETY DATA SHEET**

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
Paraffin	64742-51-4
Microcrystalline Wax	64742-42-3
Tallow	61789-97-7
Carnauba Wax	8015-86-9

PENNSYLVANIA RIGHT-TO-Know

The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAME	CAS NUMBER
Paraffin	64742-51-4
Microcrystalline Wax	64742-42-3
Tallow	61789-97-7

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are know to the state of California to causes cancer, birth defects or other reproductive harm.

CHEMICAL NAME	CAS NUMBER
No Proposition 65 chemicals exist in this product	

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

**SECTION 16 - OTHER INFORMATION**

HMIS RATINGS:	Health	0	Flammability	1	Phys. Haz.	0	PPE	A
NFPA	Health	0	Flammability	1	Reactivity	0		

VOLATILE ORGANIC COMPOUNDS (VOCs): 0 lbs / gal 0 grams / liter

LEGEND: N.A. Not Applicable N.E. Not Established N.D. Not Determined

Disclaimer: The information contained herein is base on data available. However, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.