

MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product:	DR-2, DR-2AB, DR-CH, DR-2GG, DRB-2	Trade Name:	Drill-Ease Stick Lubricant
Manufacturer:	AGS Company	Common Name:	Stick Lubricant
Street Address:	2651 Hoyt St		
City/State/Zip	Muskegon Hts., MI 49444		
Phone:	800-253-0403		
Phone:	231-733-2101		
FAX:	231-733-1784	Original Issue Date:	11/7/1981
Transportation Emergency:	CHEM-TEL	Revision No.	7 Date 1/29/2007
Phone:	800-255-3924		

SECTION 2 - COMPOSITION/ INFORMATION ON INGREDIENTS

ITEM	CAS NUMBER	WT/WT %
1 Mineral Oil Hydrotreated (Severe)	64742-52-5	15-40
2 Paraffin	64742-51-4	15-40

EXPOSURE LIMITS

ITEM	ACGIH		OSHA	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING
1	5 mg/m ³	10 mg/m ³	5 mg/m ³	N.E.
2	2 mg/m ³ fume	N.E.	2 mg/m ³ fume	N.E.

(See Section 16 for abbreviation legend)

SECTION 3 - HAZARDS IDENTIFICATION/EFFECTS OF OVEREXPOSURE

EYE CONTACT: May be irritating and can cause pain, tearing, reddening and swelling.

SKIN CONTACT: Prolonged contact may result in irritation. In molten state product can cause burns.

INHALATION: None expected.

INGESTION: This material may be harmful if swallowed.

CHRONIC HAZARDS: There are no foreseeable uses of the product that would lead to chronic exposure.

Primary Route(s) of Entry Skin and eye contact or ingestion.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists

SKIN CONTACT: Immediately flush with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

INGESTION: Get medical attention immediately. If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

MATERIAL SAFETY DATA SHEET
SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT:	380°F C.O.C.	193°C	LOWER EXPLOSIVE LIMIT:	N.D.	%
			UPPER EXPLOSIVE LIMIT:	N.D.	%
AUTOIGNITION TEMPERATURE:	N.D.				
EXTINGUISHING MEDIA:	Alcohol foam, CO ₂ Dry chemical, foam, water fog				
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Product can produce dense smoke from oils burning.				
SPECIAL FIREFIGHTING PROCEDURES:	Wear NIOSH/MSHA approved self-contained breathing apparatus and protective gear.				

SECTION 6 - ACCIDENTAL RELEASE MEASURES

RECOVERY PROCEDURES: Scrape up material and place in a chemical waste container.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Wash thoroughly after handling

STORAGE: Keep away from heat, sparks, and flame.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: No special controls needed when used in supplied form.

RESPIRATORY PROTECTION: For most conditions, no respiratory protection should be needed, however, if high vapor concentration should develop, use a NIOSH approved organic vapor respirator.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves.

EYE PROTECTION: Wear safety glasses with side shields or goggles.

OTHER PROTECTIVE EQUIPMENT: Eye wash in work area.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS/label precautions even after container is emptied because they may retain product residues. Avoid prolonged or repeated contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	572-575°F	300-302°C	VAPOR DENSITY:	Is heavier than air
ODOR	Petroleum		ODOR THRESHOLD	N.D.
APPEARANCE	Tan Wax, Solid		EVAPORATION RATE	Is slower than Butyl Acetate
SOLUBILITY IN H ₂ O	Insoluble		MELT POINT	162°F, ASTM D127
FREEZE POINT	N.A.		SPECIFIC GRAVITY	0.75
VAPOR PRESSURE	N.D.		pH @ 0.0%	N.A.
PHYSICAL STATE	Solid		VISCOSITY:	N.A.
COEFFICIENT OF WATER / OIL DISTRIBUTION:	Negligible			
	(See Section 16 for abbreviation legend)			

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Sources of ignition.

INCOMPATIBILITY: Strong acid or alkali, oxidizers and amines.

MATERIAL SAFETY DATA SHEET

HAZARDOUS DECOMPOSITION PRODUCTS Oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions

STABILITY: This product is stable under normal storage conditions.

MATERIAL SAFETY DATA SHEET

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

CHEMICAL NAME	CAS NUMBER
Paraffin	64742-51-4
Microcrystalline Wax	64742-42-3
Tallow	61789-97-7
Carnauba Wax	8015-86-9

PENNSYLVANIA RIGHT-TO-Know

The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAME	CAS NUMBER
Paraffin	64742-51-4
Microcrystalline Wax	64742-42-3
Tallow	61789-97-7

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are know to the state of California to causes cancer, birth defects or other reproductive harm.

CHEMICAL NAME	CAS NUMBER
No Proposition 65 chemicals exist in this product	

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS:	Health	0	Flammability	1	Phys. Haz.	0	PPE	A
NFPA	Health	0	Flammability	1	Reactivity	0		

VOLATILE ORGANIC COMPOUNDS (VOCs): 0 lbs / gal 0 grams / liter

LEGEND: N.A. Not Applicable N.E. Not Established N.D. Not Determined

Disclaimer: The information contained herein is base on data available. However, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.